

# PINCER TIP


## ROOF CLAMP

- The large stop surface makes it easier to insert the tips and guarantees maximum stability
- Thanks to the special movable pressure plate, it can also be used in oblique position
- Tightening torque of up to 12,0 kN | 2700 lbf



### CODES AND DIMENSIONS

CODE	opening (a)	scrapping (c)	profile (x)	weight	pcs
	[mm] [in]	[mm] [in]	[mm] [in]	[kg] [lbs]	
PINTIP60	600	120	27 x 13	2,9	1
	23 5/8	4 3/4	1 1/16 x 1/2	6.4	
PINTIP80	800	140	30 x 15	5,0	1
	31 1/2	5 1/2	1 3/16 x 9/16	11	



# GRIZZLY

## UNIVERSAL PANEL HOLDER


- Suitable for transportation of panels made of timber, OSB, MDF, non-lubricated metal, plastic, plasterboard and other materials
- Capacity up to 100 kg | 220 lbs each handle



GRIZZLY55

GRIZZLY80

GRIZZLY110



### CODES AND DIMENSIONS

CODE	opening		pcs
GRIZZLY55	0 - 55 mm	0 - 2 3/16"	2
GRIZZLY80	30 - 80 mm	1 3/16" - 3 1/8"	2
GRIZZLY110	60 - 110 mm	2 3/8" - 4 3/8"	2

### COMPLEMENTARY PRODUCTS - ACCESSORIES

CODE	description	pcs
GRIZZLYSP	1 pair of spare jaws for all GRIZZLY models	2