

- 7:1 safety factor
- Four different sizes, each available in three lengths, colour-coded

CODES AND DIMENSIONS

	CODE	L [m] [ft]	B [mm] [in]	capacity			pcs
				I	U	⊙	
1	VPR3100	3 9' 10"	50 1 15/16	1000 2200	2000 4410	800 1764	1
	VPR4100	4 13' 1"	50 1 15/16	1000 2200	2000 4410	800 1764	1
	VPR5100	5 16' 5"	50 1 15/16	1000 2200	2000 4410	800 1764	1
2	VPR3200	3 9' 10"	60 2 3/8	2000 4410	4000 8820	1600 3530	1
	VPR4200	4 13' 1"	60 2 3/8	2000 4410	4000 8820	1600 3530	1
	VPR5200	5 16' 5"	60 2 3/8	2000 4410	4000 8820	1600 3530	1
3	VPR4300	4 13' 1"	90 3 1/2	3000 6615	6000 13230	2400 5290	1
	VPR5300	5 16' 5"	90 3 1/2	3000 6615	6000 13230	2400 5290	1
	VPR6300	6 19' 8"	90 3 1/2	3000 6615	6000 13230	2400 5290	1
4	VPR4400	4 13' 1"	120 4 3/4	4000 8820	8000 17640	3200 7055	1
	VPR5400	5 16' 5"	120 4 3/4	4000 8820	8000 17640	3200 7055	1
	VPR6400	6 19' 8"	120 4 3/4	4000 8820	8000 17640	3200 7055	1



DESCRIPTION

Supplied with a certificate of conformity and user instructions. Numbered identification label with instructions for inspection and proper use of the tie rod.

FIELDS OF USE

Suitable for lifting and transporting elements of various materials, sizes and weights.