RETRACTABLE DEVICES

I FALL BLOCK

RETRACTABLE DEVICE WITH STEEL CABLE

- Equipped with ultra-resistant ABS shell, spliced metal cable with reel and double safety lever connector with twist-proof swivel
- The 10 m version is suitable for both horizontal and vertical use
- The 15 and 20 m versions comply with CE EN 360 and ATEX II 2 G c T6 standards for the regulation of equipment intended for use in potentially explosive atmospheres





 ϵ

CODES AND DIMENSIONS

CODE	standard	L		weight	pcs
		[m]	[ft]	[kg]	
FAL10	CE - EN 360	10	32' 9 3/4''	4,6	1
FAL15	CE - EN 360 - ATEX II 2 G c T6	15	49' 2 1/2''	7,2	1
FAL20	CE - EN 360 - ATEX II 2 G c T6	20	65' 7 3/8''	7,7	1

STRAP

RETRACTABLE DEVICE

- External energy absorber with protective cover that can be opened for inspection
- Equipped with swivel top anchor point and twist-lock connector with twist-proof swivel
- Suitable for both vertical and horizontal configurations
- STRAP2 version is also suitable for drop factor 2

CODES AND DIMENSIONS

CODE	standard	L		weight	pcs
		[m]	[ft]	[kg]	
STRAP2	CE - EN 360	2	6' 6 3/4''	0,9	1
STRAP6	CE - EN 360	6	19' 8 1/4''	2,4	1





STRAP2