

CONNECTORS

MULTIRING



MULTIDIRECTIONAL OPENABLE RING

- Multidirectional openable ring, ideal for semi-permanent equipment connections
- Allows the simultaneous fastening of more than two devices, with even distribution of the load
- Wide 15 mm opening, designed to facilitate the insertion of spliced ropes
- Easy to disassemble without the need for specific or complex tools



CODES AND DIMENSIONS

CODE	standard	diameter [mm]	weight [g]	<> [kN]	pcs
MULTIRING	EN 362/M	48	75	24	1

FAST LINK



FAST LINKS

- Fast link in carbon steel, half-round "D" shape ①
- Oval fast link, available in stainless steel ②
- Trapezoidal fast link, available in stainless steel ③
- Oval fast link with large stainless steel opening ④



① FASTD



② FASTOVA



③ FASTTRI



④ FASTOVAL

CODES AND DIMENSIONS

CODE	standard	weight [g]	<> [kN]	∧ [kN]	pcs
FASTD	CE - EN 362/Q - EN 12275/Q - EAC	152	50	15	1
FASTOVA	CE - EN 362/Q - EN 12275/Q - UIAA - EAC	79	40	20	1
FASTOVA2	CE - EN 362/Q - EN 12275/Q - UIAA - EAC	142	60	20	1
FASTTRI	CE - EN 362/Q - EN 12275/Q - UIAA	80	40	10	1
FASTTRI2	CE - EN 362/Q - EN 12275/Q - UIAA	155	60	30	1
FASTOVAL	-	160	-	-	1
FASTOVAL2	-	260	-	-	1