

# CONNECTORS

## MULTIRING



### MULTIDIRECTIONAL OPENABLE RING

- Multidirectional openable ring, ideal for semi-permanent equipment connections
- Allows the simultaneous fastening of more than two devices, with even distribution of the load
- Wide 15 mm opening, designed to facilitate the insertion of spliced ropes
- Easy to disassemble without the need for specific or complex tools



#### CODES AND DIMENSIONS

| CODE      | standard | diameter<br>[mm] | weight<br>[g] | <><br>[kN] | pcs |
|-----------|----------|------------------|---------------|------------|-----|
| MULTIRING | EN 362/M | 48               | 75            | 24         | 1   |

## FAST LINK



### FAST LINKS

- Fast link in carbon steel, half-round "D" shape ①
- Oval fast link, available in stainless steel ②
- Trapezoidal fast link, available in stainless steel ③
- Oval fast link with large stainless steel opening ④



① FASTD



② FASTOVA



③ FASTTRI



④ FASTOVAL

#### CODES AND DIMENSIONS

| CODE      | standard                                | weight<br>[g] | <><br>[kN] | ^<br>v<br>[kN] | pcs |
|-----------|-----------------------------------------|---------------|------------|----------------|-----|
| FASTD     | CE - EN 362/Q - EN 12275/Q - EAC        | 152           | 50         | 15             | 1   |
| FASTOVA   | CE - EN 362/Q - EN 12275/Q - UIAA - EAC | 79            | 40         | 20             | 1   |
| FASTOVA2  | CE - EN 362/Q - EN 12275/Q - UIAA - EAC | 142           | 60         | 20             | 1   |
| FASTTRI   | CE - EN 362/Q - EN 12275/Q - UIAA       | 80            | 40         | 10             | 1   |
| FASTTRI2  | CE - EN 362/Q - EN 12275/Q - UIAA       | 155           | 60         | 30             | 1   |
| FASTOVAL  | -                                       | 160           | -          | -              | 1   |
| FASTOVAL2 | -                                       | 260           | -          | -              | 1   |