

SAR

SELF-DRILLING SCREW FOR STEEL, HEXAGONAL HEAD

SELF-PERFORATING TIP


Self-perforating tip with bleeder geometry for excellent drilling capacity (up to 6 mm on steel).

EFFECTIVE

Self-tapping thread for steel and hexagonal head with dummy washer SW 10.

WATERTIGHT

Complete with integrated washer with EPDM seal for watertight fastening.



DIAMETER [mm]

3,5 8

LENGTH [mm]

25 240


ATMOSPHERIC CORROSIVITY

☒ C1 ☒ C2

MATERIAL

Zn
ELECTRO
PLATED electrogalvanized carbon steel

EPDM EPDM gasket



FIELDS OF USE


Direct fastening, without pre-drill hole, of metal structural elements and sheet metal to steel substructures maximum thickness 6,0 mm.

CODES AND DIMENSIONS


d ₁ [mm]	d _{UK} [mm]	CODE	L [mm]	A [mm]	s [mm]	pcs
6,3 SW 10	12,5	SAR6322	22	0,5 ÷ 9	0,6 ÷ 1,5	100
		SAR6360	60	0 ÷ 47	2 ÷ 6	100
		SAR6370	70	14 ÷ 57	2 ÷ 6	100
		SAR6380	80	24 ÷ 67	2 ÷ 6	100
		SAR63100	100	44 ÷ 87	2 ÷ 6	100
		SAR63120	120	64 ÷ 107	2 ÷ 6	100
		SAR63140	140	84 ÷ 127	2 ÷ 6	100
		SAR63160	160	104 ÷ 147	2 ÷ 6	100
		SAR63180	180	124 ÷ 167	2 ÷ 6	100
		SAR63200	200	144 ÷ 187	2 ÷ 6	100

s thickness that can be drilled, metal plate (steel or aluminium)

GEOMETRY



Nominal diameter	d ₁	[mm]	6,3
Wrench size	SW	[mm]	SW 10
Head diameter	d _{UK}	[mm]	12,50
Diameter of washer	D	[mm]	15,70



TRAPEZOIDAL METAL SHEET ROOFS

Thanks to its steel drilling capability and the watertightness of the combined washer, it is the ideal choice for application on trapezoidal sheet metal.