

COMPRESSOR 50

CE
DM 2006/42/CE

LARGE OIL-FREE COMPRESSOR WITH 50 L RUSTPROOF TANK

LONG SERVICE LIFE GUARANTEED

The special internal coating of the tank protects against corrosion caused by condensation, ensuring strength and durability even under intensive use.

GREATER STABILITY ON UNEVEN GROUND

Thanks to the lower centre of gravity, the horizontal compressor is more stable and less prone to tipping, making it particularly suitable for construction sites with uneven terrain.

LARGE CAPACITY

Ideal for large compressed-air devices with high air consumption or for simultaneous operation of two medium-sized tools thanks to the dual connections.



CODES AND DIMENSIONS

CODE	description	pcs
1 COMP50	compressor with 50 L rustproof tank	1

TECHNICAL DATA

Properties	values
Supply voltage	230 V
Rated power	1,1 kW
Frequency	50 Hz
Maximum operating pressure	8 bar 115 psi
Safety valve	10 bar 145 psi
Noise level	69 dB
Rotation speed	1400 rpm
Tank volume	50 l
Inlet air flow rate	300 l/min
Outlet air flow rate	170 l/min
Total weight	48 kg 105 lbs
Dimensions (L x P x H)	800 x 350 x 650 mm 31 1/2" x 13 3/4" x 25 9/16"